



Image shown may not reflect actual package.

## STANDBY

**500 kW 625 kVA  
60 Hz 1800 rpm 480 Volts**

Caterpillar is leading the power generation marketplace with Power Solutions engineered to deliver unmatched flexibility, expandability, reliability, and cost-effectiveness.

## FEATURES

### FUEL/EMISSIONS STRATEGY

- EPA Tier 2 and Low Emissions

### DESIGN CRITERIA

- The generator set accepts 100% rated load in one step per NFPA 110 and meets ISO 8528-5 transient response.

### UL 2200

- UL 2200 listed packages available. Certain restrictions may apply. Consult with your Caterpillar Dealer.

### FULL RANGE OF ATTACHMENTS

- Wide range of bolt-on system expansion attachments, factory designed and tested
- Flexible packaging options for easy and cost effective installation

### SINGLE-SOURCE SUPPLIER

- Fully prototype tested with certified torsional vibration analysis available

### WORLDWIDE PRODUCT SUPPORT

- Caterpillar® dealers provide extensive post sale support including maintenance and repair agreements
- Caterpillar dealers have over 1,600 dealer branch stores operating in 200 countries
- The Cat® S•O•SSM program cost effectively detects internal engine component condition, even the presence of unwanted fluids and combustion by-products

### CAT® C15 ATAAC DIESEL ENGINE

- Utilizes ACERT™ Technology
- Reliable, rugged, durable design
- Field-proven in thousands of applications worldwide
- Four-stroke diesel engine combines consistent performance and excellent fuel economy with minimum weight
- Electronic engine control

### CAT GENERATOR

- Matched to the performance and output characteristics of Caterpillar engines
- Load adjustment module provides engine relief upon load impact and improves load acceptance and recovery time
- UL 1446 Recognized Class H insulation

### CAT EMCP 3 SERIES CONTROL PANELS

- Simple user friendly interface and navigation
- Scalable system to meet a wide range of customer needs
- Integrated Control System and Communications Gateway

# STANDBY 500 ekW 625 kVA

60 Hz 1800 rpm 480 Volts



## FACTORY INSTALLED STANDARD & OPTIONAL EQUIPMENT

System	Standard	Optional
Air Inlet	<ul style="list-style-type: none"><li>• Light Duty Air filter</li></ul>	<ul style="list-style-type: none"><li>• Canister Style Air Cleaners</li><li>• Air Cleaner - single stage</li><li>• Dual element</li><li>• Heavy duty</li></ul>
Cooling	<ul style="list-style-type: none"><li>• Radiator package mounted(50°C)</li><li>• Coolant drain line with valve terminated at edge of base</li><li>• Fan and belt guards</li><li>• Coolant level sight gauge</li><li>• Caterpillar Extended Life Coolant</li></ul>	<ul style="list-style-type: none"><li>• Radiator removal</li><li>• Radiator duct flange &amp; guard</li></ul>
Exhaust	<ul style="list-style-type: none"><li>• Dry exhaust manifold</li><li>• Flanged faced outlets</li><li>• Stainless Steel Flex with split-cuff connection</li></ul>	<ul style="list-style-type: none"><li>• Mufflers</li><li>• Manifold &amp; Turbocharger guards</li><li>• Elbows</li></ul>
Fuel	<ul style="list-style-type: none"><li>• Primary fuel filter with integral water separator</li><li>• Secondary fuel filters</li><li>• Fuel priming pump</li><li>• Engine fuel transfer pump</li><li>• Flex fuel lines</li><li>• Fuel cooler*</li></ul> <p>*Not included with packages without radiators</p>	<ul style="list-style-type: none"><li>• Integral UL listed fuel tank base</li><li>• Manual transfer pump</li><li>• Fuel level switch</li></ul>
Generator	<ul style="list-style-type: none"><li>• Class H insulation</li><li>• R448 voltage regulator with load adjustment module</li><li>• IP23 Protection</li></ul>	<ul style="list-style-type: none"><li>• CDVR with KVAR/PF control</li><li>• Oversize and premium generators</li><li>• Bearing/Stator temperature detection (premium generator)</li><li>• 3 phase sensing</li><li>• Anti-condensation space heaters</li><li>• Cable access box</li><li>• Reactive droop</li></ul>
Power Termination	<ul style="list-style-type: none"><li>• Power Terminator Strips Mounted inside Power Center</li><li>• Segregated low voltage wiring panel</li></ul>	<ul style="list-style-type: none"><li>• Circuit breakers, UL listed, 3 pole</li><li>• Circuit breakers, IEC compliant, 3 pole</li><li>• Circuit breaker Shunt trip</li><li>• Circuit breaker Auxillary contact</li><li>• Top &amp; bottom power cable entry</li><li>• Floor standing UL breakers</li></ul>
Governor	<ul style="list-style-type: none"><li>• ADEM™A4</li></ul>	<ul style="list-style-type: none"><li>• Load share module</li></ul>
Control Panels	<ul style="list-style-type: none"><li>• EMCP 3.1 (rear mounted)</li><li>• Speed adjust</li><li>• Emergency stop pushbutton</li><li>• Voltage adjust</li></ul>	<ul style="list-style-type: none"><li>• EMCP 3.2 &amp; EMCP 3.3 (can be RH mounted)</li><li>• Local annunciator modules (NFPA 99/110)</li><li>• Remote annunciator modules (NFPA 99/110)</li><li>• Discrete I/O module</li></ul>
Lube	<ul style="list-style-type: none"><li>• Lubricating oil and filter</li><li>• Oil drain line with valves</li><li>• Fumes disposal</li><li>• Gear type lube oil pump</li></ul>	<ul style="list-style-type: none"><li>• Manual sump pump</li></ul>
Starting/Charging	<ul style="list-style-type: none"><li>• 24 volt starting motor</li><li>• Battery with rack and cables (dry)</li><li>• 45 amp charging alternator</li></ul>	<ul style="list-style-type: none"><li>• Jacket water heater with shut off valves</li><li>• Block heater</li><li>• Ether starting aids</li><li>• Battery disconnect switch</li><li>• Battery chargers ( 5 &amp; 10 amp)</li><li>• Oversized batteries</li></ul>
General	<ul style="list-style-type: none"><li>• Paint - Caterpillar yellow except rails and radiators gloss black</li><li>• Flywheel and flywheel housing - SAE No.1</li></ul>	

# STANDBY 500 ekW 625 kVA

60 Hz 1800 rpm 480 Volts



## SPECIFICATIONS

### CAT GENERATOR

Frame size.....LC6114F  
Excitation..... Self Excitation  
Pitch..... 0.6667  
Number of poles..... 4  
Number of bearings..... Single Bearing  
Number of Leads..... 12  
Insulation..... UL 1446 Recognized Class H with  
tropicalization and antiabrasion  
- Consult your Caterpillar dealer for available voltages  
IP Rating..... IP23  
Alignment..... Pilot Shaft  
Overspeed capability..... 125% of rated  
Wave form Deviation (Line to Line)..... 2%  
Voltage regulator..... Single phase sensing with  
selectible volts/Hz  
Voltage regulation..... Less than +/- 1/2% (steady state)  
Less than +/- 1/2% (w/ 3% speed change)  
Telephone influence factor..... Less than 50  
Harmonic Distortion..... Less than 5%

### CAT DIESEL ENGINE

C15 ATAAC, L-6, 4-stroke water-cooled diesel  
Bore..... 137.20 mm (5.4 in)  
Stroke..... 171.40 mm (6.75 in)  
Displacement..... 15.20 L (927.56 in<sup>3</sup>)  
Compression Ratio..... 16.1:1  
Aspiration..... ATAAC  
Fuel System..... MEUI  
Governor Type..... Caterpillar ADEM control system

### CAT EMCP 3 CONTROL PANELS

- EMCP 3.1 (Standard)
- UL/CSA/CE
- NEMA 1, IP22 enclosure
- Run/Auto/Stop control
- True RMS metering, 3-phase
- Speed Adjust
- Vandal cover (option)
- Voltage adjust
- Digital Indication for:
  - RPM
  - Operating hours
  - Oil Pressure
  - Coolant temperature
  - System DC volts
  - L-L volts, L-N volts, phase amps, Hz
  - ekW, kVA, kVAR, kW-hr, %kW, PF, (EMCP3.2/3.3)
- Shutdowns with common indicating light for:
  - Low oil pressure
  - High coolant temperature
  - Low coolant level
  - Overspeed
  - Emergency stop
  - Failure to start (overcrank)
- Programmable protective relaying functions: (EMCP 3.2 & 3.3)
  - Under and over voltage
  - Under and over frequency
  - Reverse power
  - Overcurrent
- MODBUS isolated data link (RS-485 half-duplex EMCP 3.2 & 3.3)

## TECHNICAL DATA

Open Generator Set - - 1800 rpm/60 Hz/480 Volts	DM8155	
<b>Tier 2 and Low Emissions</b>		
<b>Generator Set Package Performance</b> Genset Power rating @ 0.8 pf Genset Power rating with fan	625 kVA 500 ekW	
<b>Fuel Consumption</b> 100% load with fan 75% load with fan 50% load with fan	138.5 L/hr 106.1 L/hr 88.1 L/hr	36.6 Gal/hr 28.0 Gal/hr 23.3 Gal/hr
<b>Cooling System<sup>1</sup></b> Air flow restriction (system) Air flow (max @ rated speed for radiator arrangement) Engine Coolant capacity with radiator/exp. tank Engine coolant capacity Radiator coolant capacity	0.12 kPa 822 m³/min 57.8 L 20.8 L 37.0 L	0.48 in. water 29029 cfm 15.3 gal 5.5 gal 9.8 gal
<b>Inlet Air</b> Combustion air inlet flow rate	39.5 m³/min	1394.9 cfm
<b>Exhaust System</b> Exhaust stack gas temperature Exhaust gas flow rate Exhaust flange size (internal diameter) Exhaust system backpressure (maximum allowable)	505.6 °C 108.8 m³/min 152.4 mm 6.8 kPa	942.1 °F 3842.2 cfm 6.0 in 27.3 in. water
<b>Heat Rejection</b> Heat rejection to coolant (total) Heat rejection to exhaust (total) Heat rejection to atmosphere from engine Heat rejection to atmosphere from generator	189 kW 486 kW 119 kW 29.1 kW	10748 Btu/min 27639 Btu/min 6768 Btu/min 1654.9 Btu/min
<b>Alternator<sup>2</sup></b> Motor starting capability @ 30% voltage dip Frame Temperature Rise	1428 skVA LC6114F 130 °C	234 °F
<b>Emissions (Nominal)<sup>3</sup></b> NOx g/hp-hr CO g/hp-hr HC g/hp-hr PM g/hp-hr	5.74 g/hp-hr .4 g/hp-hr .01 g/hp-hr .018 g/hp-hr	

<sup>1</sup> For ambient and altitude capabilities consult your Caterpillar dealer. Air flow restriction (system) is added to existing restriction from factory.

<sup>2</sup> Generator temperature rise is based on a 40° C (104° F) ambient per NEMA MG1-32.

<sup>3</sup> Emissions data measurement procedures are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NOx. Data shown is based on steady state operating conditions of 77°F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations. Emissions data is based on 100% load and thus cannot be used to compare to EPA regulations which use values based on a weighted cycle.

# STANDBY 500 ekW 625 kVA

60 Hz 1800 rpm 480 Volts



## RATING DEFINITIONS AND CONDITIONS

---

**Meets or Exceeds International Specifications:** AS1359, CSA, IEC60034, ISO3046, ISO8528, NEMA MG 1-33, UL508A, 98/37/EC

**Standby** - Output available with varying load for the duration of the interruption of the normal source power. Average power output is 70% of the standby power rating. Typical operation is 200 hours per year, with maximum expected usage of 500 hours per year. Standby power in accordance with ISO8528. Fuel stop power in accordance with ISO3046. Standby ambients shown indicate ambient temperature at 100% load which results in a coolant top tank temperature just below the shutdown temperature.

**Ratings** are based on SAE J1995 standard conditions. These ratings also apply at ISO3046 standard conditions. **Fuel rates** are based on fuel oil of 35° API [16° C (60° F)] gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.). Additional ratings may be available for specific customer requirements, contact your Caterpillar representative for details. For information regarding Low Sulfur fuel and Biodiesel capability, please consult your Caterpillar dealer.

**STANDBY 500 ekW 625 kVA**  
60 Hz 1800 rpm 480 Volts



**DIMENSIONS**

---

Package Dimensions		
Length	3775.1 mm	148.63 in
Width	1110.0 mm	43.7 in
Height	2091.0 mm	82.32 in
Weight	3881 kg	8,556 lb

NOTE: For reference only - do not use for installation design. Please contact your local dealer for exact weight and dimensions. (General Dimension Drawing #2781049).